



52 Hess Road, Leola, PA 17540
 Ph: 717-656-6241 | Fx: 717-656-5458

Specification	DS6000DX	DS5000DX	DS5000	DS4000	LG300
Hopper Capacity	2000 lbs	1000 lbs	1000 lbs	500 lbs	300 lbs
Cubic Ft. Capacity	23.55	13.02	12.68	6.37	3.85
Empty Weight	790 lbs	450 lbs	210 lbs	164 lbs	65 lbs
Shipping Weight	950 lbs	510 lbs	270 lbs	210 lbs	69 lbs
Drop Width	72"	60"	60"	48"	36"
Tire Tracking Width	87"	72"	68.5"	55.5"	40.5"
Tire & Wheel Oad	26"	24"	16"	16"	8"
Overall Width	97"	78"	74"	62.25"	44.5"
OAL w/ Hitch Shortened	86.5"	57.5"	58.5"	58.75"	44"
OAL w/Hitch Extended	94.5"	64.5"	N/A	N/A	N/A
Hitch Type	Pin	Pin	Pin	Pin	Pin
Height	39.5"	34"	33.5"	26.5"	23.5"
Height w/ Handle	41"	39"	33.5"	31.5"	N/A
Ground Clearance	11"	9"	5"	5"	3"
Tire Size	9.5L-15SL	175/80-13	18x6.50-8	18x16.50-8	4.10/3.50-6
Hopper Construction	11 ga	14 ga	14 ga	14 ga	18 ga
Beater Auger Driven	Ground	Ground	Ground	Ground	Ground
Standard Warranty	3 year	3 year	3 year	3 year	1 year
Rental Warranty	1 year	1 year	1 year	1 year	none

Option	DS6000DX	DS5000DX	DS5000	DS4000	LG300
175/80-13 Wheel & Tire Kit	N/A	N/A	X	X	N/A
Jack Stand	X	X	X	X	N/A
Ball Hitch	X	X	X	X	X
Hyd. Gate Cylinder Kit	X	X	N/A	N/A	N/A
Tarp	X	X	X	X	X
Fertilizer Gate/Screen	X	X	X	X	X



Drop Spreaders
by JR Metal





DS 6000 DX

DS 5000 DX

DS 5000

DS 4000

LG 300

Hopper Capacity: 2000 lbs
Drop width: 72"

FEATURES

- › Heavy-duty 11 gauge & 1/4" steel
- › Implement ag tire & rim
- › Accessible grease zerks
- › Greaseable pillow block bearings
- › Abrasive blasted & powder coated
- › Dual ground driven beaters with lock-out hubs
- › Seven position aperture & closed
- › Adjustable slotted pan
- › Safety screen
- › Three position adjustable pin hook-up

BENEFITS

- › All welded construction
- › Designed for broad load distribution/maximum flotation
- › Tough powder coat, longer lasting
- › Precise spreading to match ground speed & terrain
- › Capable of spreading variable amounts
- › Dispenses bulk ag lime
- › Assures accurate spread pattern
- › Minimal waste of material
- › Screen helps reduce foreign objects from entering spreader
- › Quick, easy cleaning

Hopper Capacity: 1000 lbs
Drop width: 60"

FEATURES

- › Heavy-duty 14 gauge & 3/16" steel
- › Heavy-duty tires & rims
- › Accessible grease zerks
- › Greaseable bronze flange bearings
- › Abrasive blasted & powder coated
- › Dual ground driven beaters with lock-out hubs
- › Seven position aperture & closed
- › Adjustable slotted pan
- › Safety screen
- › Three position adjustable pin hook-up

BENEFITS

- › All welded construction
- › Designed to accept stresses of heavy load
- › Tough powder coat, longer lasting
- › Precise spreading to match ground speed & terrain
- › Capable of spreading variable amounts
- › Dispenses bulk ag lime
- › Assures accurate spread pattern
- › Minimal waste of material
- › Screen helps reduce foreign objects from entering spreader
- › Quick, easy cleaning

Hopper Capacity: 1000 lbs
Drop width: 60"

FEATURES

- › Heavy-duty 14 gauge steel
- › All-purpose tires & rims
- › Accessible grease zerks
- › Greaseable bronze flange bearings
- › Abrasive blasted & powder coated
- › Single ground driven beater
- › Five position aperture & closed
- › Adjustable slotted pan
- › Safety screen
- › Pin hook-up

BENEFITS

- › All welded construction
- › Designed to accept stresses of heavy load
- › Tough powder coat, longer lasting
- › Precise spreading to match ground speed & terrain
- › Capable of spreading variable amounts
- › Dispenses bulk ag lime
- › Assures accurate spread pattern
- › Minimal waste of material
- › Screen helps reduce foreign objects from entering spreader
- › Quick, easy cleaning

Hopper Capacity: 500 lbs
Drop width: 48"

FEATURES

- › Heavy-duty 14 gauge steel
- › All-purpose tires & rims
- › Accessible grease zerks
- › Greaseable bronze flange bearings
- › Abrasive blasted & powder coated
- › Single ground driven beater
- › Five position aperture & closed
- › Adjustable slotted pan
- › Safety screen
- › Pin hook-up

BENEFITS

- › All welded construction
- › Designed to accept stresses of heavy load
- › Tough powder coat, longer lasting
- › Precise spreading to match ground speed & terrain
- › Capable of spreading variable amounts
- › Dispenses bulk ag lime
- › Assures accurate spread pattern
- › Minimal waste of material
- › Screen helps reduce foreign objects from entering spreader
- › Quick, easy cleaning

Hopper Capacity: 300 lbs
Drop width: 36"

FEATURES

- › Heavy-duty 18 gauge steel
- › All-purpose tires & rims
- › Oil impregnated bronze bushings
- › Single ground driven beater
- › Abrasive blasted & powder coated
- › Pin hook-up
- › Variable position aperture & closed
- › Adjustable slotted pan
- › Safety screen

BENEFITS

- › Bolted together design, easy assembly
- › Provides 3" ground clearance
- › Tough, powder coat, longer lasting
- › Pull with small lawn tractor
- › Capable of spreading variable amounts
- › Dispenses bagged lime
- › Assures accurate spread pattern
- › Minimal waste of material
- › Screen helps reduce foreign objects from entering spreader
- › Quick, easy cleaning

Dispensing Materials (All Spreaders except LG 300)

All types of dry lime including pelletized lime, Gypsum, Fertilizer, Dry peat moss, Sand, Salt, Snow/ice management products, Dry soil amendment products, Dry athletic field products, Dry top dressing products, fungicides, Dry chemicals.

